

# ZR61KC-TFD



HCFC, R-22, Mid Point, 50 Hz, 3 - Phase, 380/420 V

Air Conditioning

**Production Status:** Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies representative for international availability.

## Performance

Evap(°F)/Cond(°F)	45/130	45/100
RG(°F)/Liq(°F)	65/115	65/85
Capacity (Btu/hr):	49700	59000
Power (Watts):	4430	3200
Current (Amps):	8.2	6.5
EER (Btu/Wh):	11.2	18.4
Mass Flow (lbs/hr):	730.0	760.0
Sound Power(dBA):	71 Ave	76 Max
Vibration (mils(peak-peak)):	2.0 Ave	3.0 Max
Record Date:	2004-03-11	

## Mechanical

Number of Cylinders:	0	Displ (in <sup>3</sup> /Rev):	5.04
Bore Size (in):	0.0	Displ (ft <sup>3</sup> /hr):	507.4977
Stroke (in):	0.0		
Overall Length (in):	9.48	Mounting Length (in):	7.5
Overall Width (in):	9.71	Mounting Width(in):	7.5
Overall Height (in):	17.75	Mounting Height (in):	18.0*
Suction Size (in):	7/8 Stub		
Discharge Size (in):	1/2 Stub		
Initial Oil Charge (oz):	66		
Oil Recharge (oz):	62		
Net Weight (lbs):	79.5		
Internal Free Volume (in <sup>3</sup> ):	272.0		
HorsePower	5.0		
* Overall compressor height on Copeland Brand Product's specified mounting grommets.			

## Electrical

LRA-High*:	65.5	MCC (Amps):	14.0	UL File No.:	SA-2337
LRA-Half Winding:		RPM:	2900	UL File Date:	26-Jul-1993
LRA-Low*:	58.6	Max Operating Current:	10.0	CSA File No.:	LR3104C
RLA(=MCC/1.4; use for contactor selection):	10				
RLA (=MCC/1.56; use for breaker & wire size selection):	9				
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

## Alternate Applications

Refrigerant	Frequency(Hz)	Phase	Voltage	Application
R-22 HCFC	60	3	460	Air Conditioning